





SECTION 2: GLASS FIXINGS


INDEX

Product	PAGE
RUN OUT STOCK	
Covered Counter Sunk Bushes - 304SSS Cap	2.1
Anchor Spanner	2.2
Button Head Fixings	2.3
Button Heads, Spacers, Lagscrew, Threaded Rod	2.4
Nuts, Washer, Gaskets	2.5
Button Head Standoff Anchors	2.6
Covered Countersunk Standoff Anchors	2.7

GLASS FIXINGS - COVERED COUNTERSUNK BUSHES


RUN OUT STOCK ONLY

Set Screws Covered Bushes	Code	Description	Price
 <p>Diagram showing a stainless steel covered bush (CCB4) with an M4 set screw. The bush has a countersunk end and a threaded section.</p>	CCB4	STAINLESS STEEL COVERED BUSH to suit 6mm glass CCB4 covered bush only Specify wood or metal fix screw $\text{ØA} = 16\text{mm}$ $\text{ØB} = 7\text{mm}$	
 <p>Diagram showing a stainless steel covered bush (CCB6) with an M6 set screw. The bush has a countersunk end and a threaded section.</p>	CCB6	STAINLESS STEEL COVERED BUSH to suit 8 & 10mm glass CCB6 covered bush only Specify wood or metal fix screw $\text{ØA} = 22\text{mm}$ $\text{ØB} = 10\text{mm}$	
 <p>Diagram showing a stainless steel covered bush (CCB8) with an M8 set screw. The bush has a countersunk end and a threaded section.</p>	CCB8	STAINLESS STEEL COVERED BUSH to suit 8, 10 & 12mm glass CCB8 covered bush only Specify wood or metal fix screw $\text{ØA} = 26\text{mm}$ $\text{ØB} = 14\text{mm}$	
 <p>Diagram showing a stainless steel covered bush (CCB10) with an M10 set screw. The bush has a countersunk end and a threaded section.</p>	CCB10	STAINLESS STEEL COVERED BUSH to Suit 10, 12 & 15mm glass CCB10 covered bush only socket screw $\text{ØA} = 30\text{mm}$ $\text{ØB} = 18\text{mm}$	






HOLE PREPARATION






GLASS FIXINGS - ANCHOR SPANNERS

Produce	Code	Description	Price
	<p>SP19-50</p>	<p>ANCHOR SPANNER TO SUIT 19mm to 50mm diameter Anchors</p>	

GLASS FIXINGS - BUTTON HEADS

Button Head Fixings	Code	Description 304 stainless steel buttons	Price
 <p>"X" equals tightened thread length between button heads.</p>	DB19-X	Replace "X" in code with required length of thread between buttons when tightened. DOUBLE BUTTON HEADS 19mm diameter	
	DB25-X	DOUBLE BUTTON HEADS 25mm diameter	
	DB32-X	DOUBLE BUTTON HEADS 32mm diameter	
	All double button heads are supplied with two nylon washers and sleeve.		
 <p>"X" equals length of rod.</p>	BT19-X	Replace "X" in Code with required length of threaded rod. Stock length 18mm. BUTTON HEAD 19mm diameter	
	BT25-X	BUTTON HEAD 25mm diameter	
	BT32-X	BUTTON HEAD 32mm diameter	
	All single button heads are supplied with two nylon washers and sleeve.		
 <p>"X" equals length of Lag Screw. Minimum length 25mm Maximum length 55mm. Note: 50mm diameter minimum length 50mm</p>	BL19-X	Replace "X" in Code with required length of Lag Screw. BUTTON HEAD 19mm diameter with Lag Screw	
	BL25-X	BUTTON HEAD 25mm diameter with Lag Screw	
	BL32-X	BUTTON HEAD 32mm diameter with Lag Screw	
	All single button heads are supplied with two nylon washers and sleeve.		
		Note: Lag Screw and Rod sizes	
		19mm Button - M6 } Minimum Lag Screw length 25mm	
		25mm Button - M6 } Minimum Lag Screw length 30mm	
		32mm Button - M8 } Minimum Lag Screw length 30mm	
		38mm Button - M8 } Minimum Lag Screw length 50mm	
		50mm Button - M10 - Minimum Lag Screw length 50mm	

GLASS FIXINGS - BUTTON HEADS & SPACERS

Product	Code	Description	Price
		304SSS Button with LDPE Washer & Sleeve	
	BH19	19mm diameter Button Head M6 thread	
	BH25	25mm diameter Button Head M6 thread	
	BH32	32mm diameter Button Head M8 thread	
		304SSS Spacer with LDPE Washer	
	SP19-5	19mm diameter x 5mm Spacer 7mm hole	
	SP25-5	25mm diameter x 5mm Spacer 7mm hole	
	SP32-5	32mm diameter x 5mm Spacer 8.5mm hole	
		304SSS Spacer with LDPE Washer	
	SP19-10	19mm diameter x 10mm Spacer 7mm hole	
	SP25-10	25mm diameter x 10mm Spacer 7mm hole	
	SP32-10	32mm diameter x 10mm Spacer 8.5mm hole	
		Lag Screws	
	M6-50ZL	M6 x 50mm zinc plated	
	M8-50ZL	M8 x 50mm zinc plated	
		Threaded Rods	
	M6-R25	M6 x 25mm stainless steel 304	
	M6-R32	M6 x 32mm stainless steel 304	
	M6-R60	M6 x 60mm stainless steel 304	
	M8-R25	M8 x 25mm stainless steel 304	
	M8-R60	M8 x 60mm stainless steel 304	


Merchant Price List	
---------------------	--

GLASS FIXINGS - BUTTON HEAD STANDOFF ANCHORS

RUN OUT STOCK ONLY

Code	Description 304 Satin Stainless Steel Anchors	Price
GSBH - 19 x 25	STAINLESS STEEL BUTTON HEAD 19mm diameter x 25mm standoff	
GSBH - 25 x 25	STAINLESS STEEL BUTTON HEAD 25mm diameter x 25mm standoff	
GSBH - 32 x 25	STAINLESS STEEL BUTTON HEAD 32mm diameter x 25mm standoff	
GSBH - 32 x 50	STAINLESS STEEL BUTTON HEAD 32mm diameter x 50mm standoff	

- When ordering, specify 50mm threaded rod or woodfix lag screw for wall fixing.
- Anchor diameter 19mm and 25mm – use M6 threaded rod and lag screw.
- Anchor diameter 32mm – use M8 threaded rod and lag screw.




Please note

Custom size anchors available on request.
Simply fill in the order/enquiry form (page 2.9) and fax for quotations and orders.
For custom sizes allow 7 working days lead time.

GLASS FIXINGS - COVERED COUNTERSUNK STANDOFF ANCHORS

Code	Description 304 Satin Stainless Steel Anchors	Price
GSCC - 19 x 25	STAINLESS STEEL COVERED COUNTERSUNK 19mm diameter x 25mm standof	
GSCC - 25 x 25	STAINLESS STEEL COVERED COUNTERSUNK 25mm diameter x 25mm standoff	
GSCC - 32 x 25	STAINLESS STEEL COVERED COUNTERSUNK 32mm diameter x 25mm standoff	

- When ordering, specify 50mm threaded rod or woodfix lag screw for wall fixing.
- Anchor diameter 19mm and 25mm – use M6 threaded rod, lag screw and CCB6 Bush.
- Anchor diameter 32mm – use M8 threaded rod, lag screw and CCB8 Bush.



Please note

Custom size anchors available on request. P.O.A.
Simply fill in the order/enquiry form (page 2.9) and fax for quotations and orders.
For custom sizes allow 7 working days lead time.